Manila

COLOR FASTNESS

PROPERTY	TEST METHOD	PERFORMANCE
Dry rub fastness, 50 cycles	EN ISO 11640	≥ 3 Grey Scale
Wet rub fastness, 20 cycles	EN ISO 11640	≥ 3 Grey Scale
Artificial solution rub fastness, 20 cycles	EN ISO 11640 / EN ISO 11641	≥ 2 Grey Scale
Fastness to light	EN ISO 105-B02 (Met. 3)	≥ 2/3 Blue Scale

PHYSICAL CHARACTERISTICS

PROPERTY	TEST METHOD	PERFORMANCE
Tear strength	EN ISO 3377-1	> 20 N

ADVICES FOR CLEANING AND MAINTENANCE

Avoid any direct exposure to the sun

Dust regularly with a soft and dry cloth

Keep the leather away from direct heat

Flammability test: EN 1021-1, EN 1021-2, BS5852:Source 0, BS5852:Source 1, Cal TB117, NFPA 260/UFAC*

* The tests are performed periodically on the leather samples in accordance to the annual audit plan. The standardized production process ensures the conformance to the requirement

THE ARTICLE IS MANUFACTURED IN COMPLIANCE WITH THE REACH DIRECTIVE AND COMPLIES WITH THE LATEST VERSION OF THE RSL_DANI

SYSTEM CERTIFICATIONS



COMPANY WITH ENVIRONMENTAL SYSTEM CERTIFIED BY DNV ISO 14001 COMPANY WITH SAFETY SYSTEM CERTIFIED BY DNV ISO 45001 COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV ISO 9001 COMPANY WITH
INFORMATION SECURITY
MANAGEMENT SYSTEM
CERTIFIED BY DNV
ISO/IEC 27001
VALID FOR IT
DEPARTMENT

COMPANY WITH ENERGY MANAGEMENT SYSTEM CERTIFIED BY DNV ISO 50001













WEL

PRODUCT CERTIFICATIONS









EPD & PROCESS EPD ISO 14025

LEATHER FROM ITAL FULL CYCLE UNI EN 16484:2015

TRACEABIL TRC SC 4

CARBON FOOTPRIN

AWARDS



JOIN IN







PRODUCT COLORS ARE SUBJECT TO CHANGE, THEIR AVAILABILITY WILL BE CONFIRMED AT THE MOMENT OF THE ORDER.



TESTS ARE PERFORMED PERIODICALLY IN ACCORDANCE WITH THE MOST RECENT PROVISIONS. TO VIEW THE LATEST VERSION: CLICK HERE.