

Como

COLOR FASTNESS

PROPERTY	TEST METHOD	PERFORMANCE
Dry rub fastness, 200 cycles	EN ISO 11640	≥ 4 Grey Scale
Wet rub fastness, 50 cycles	EN ISO 11640	≥ 3/4 Grey Scale
Artificial solution rub fastness, 30 cycles	EN ISO 11640 / EN ISO 11641	≥ 3/4 Grey Scale

PHYSICAL CHARACTERISTICS

PROPERTY	TEST METHOD	PERFORMANCE
Adhesion of finish dry	EN ISO 11644	≥ 2 N/10mm
Tear strength	EN ISO 3377-1	≥ 20 N
Flex resistance, 30.000 cycles	EN ISO 5402-1	No cracks

ADVICES FOR CLEANING AND MAINTENANCE

Avoid any direct exposure to the sun Dust regularly with a soft and dry cloth

Keep the leather away from direct heat

Flammability test: EN 1021-1, EN 1021-2, BS5852:Source 0, BS5852:Source 1, Cal TB117, NFPA 260/UFAC*

* The tests are performed periodically on the leather samples in accordance to the annual audit plan. The standardized production process ensures the conformance to the requirement

THE ARTICLE IS MANUFACTURED IN COMPLIANCE WITH THE REACH DIRECTIVE AND COMPLIES WITH THE LATEST VERSION OF THE RSL_DANI

SYSTEM CERTIFICATIONS



PRODUCT CERTIFICATIONS



AWARDS



JOIN IN



DANI S.p.A.
Z.I. Via della Concia, 186
36071 Arzignano (VI) Italy
Tel. +39 0444 454111
www.gruppodani.com



PRODUCT COLORS ARE SUBJECT TO CHANGE, THEIR AVAILABILITY WILL BE CONFIRMED AT THE MOMENT OF THE ORDER.



TESTS ARE PERFORMED PERIODICALLY IN ACCORDANCE WITH THE MOST RECENT PROVISIONS. TO VIEW THE LATEST VERSION: [CLICK HERE.](#)